

Current Chum Operation as of December 16, 2015, at 9am

1. EFFECTIVE SATURDAY, NOVEMBER 7, 2015, AT 0600 HOURS, UNTIL FURTHER NOTICE, OPERATE BONNEVILLE DAM TAILWATER IN THE FOLLOWING ORDER OF OPERATING RANGES AS PROJECT OUTFLOW INCREASES.
2. DURING ALL HOURS, OPERATE PROJECT OUTFLOW TO PROVIDE A TAILWATER ELEVATION IN THE RANGE OF 11.5–12.5 FEET.
3. IF NECESSARY TO INCREASE PROJECT OUTFLOW, TAILWATER MAY BE OPERATED UP TO 13.0 FEET AT ANY TIME. RETURN TO TAILWATER RANGE OF 11.5–12.5 FEET WHENEVER POSSIBLE.
4. THEN IF NECESSARY TO INCREASE PROJECT OUTFLOW, THE TAILWATER MAY BE OPERATED UP TO 16.5 FEET DURING NIGHTTIME HOURS (1700-0600). CONCENTRATE HIGHEST ELEVATIONS AROUND 2400 HOURS.
5. THEN IF NECESSARY TO INCREASE PROJECT OUTFLOW, THE TAILWATER MAY BE OPERATED UP TO 18.5 FEET DURING NIGHTTIME HOURS (1700-0600).
6. THEN IF INCREASING RIVER FLOW PRECLUDES THE ABILITY TO MANAGE TAILWATER WITHIN THE STEPS ABOVE, OPERATE TO PROVIDE A TAILWATER IN THE RANGE OF 13.0–16.5 FEET DURING DAYTIME HOURS (0600-1700) AND UP TO THE MAXIMUM WITHIN PROJECT 24-HOUR RAMP RATE LIMITS DURING NIGHTTIME HOURS (1700-0600). CONTINUE TO OPERATE THE BONNEVILLE TAILWATER WITHIN THESE CRITERIA UNLESS OTHERWISE DIRECTED BY RCC.